

# Handpieces & Portable Power Supplies

## Light-Weight | Tough | Ergonomic

Seedorff offers a large assortment of Miniature Weld Guns for Light Duty and Heavy Duty Tack Welding. Hand Held Poke-Tack, Push Guns and Air-Operated Pincer Guns are offered for a wide variety of applications including: Pre-Tack Braze, Foil Tack and Honeycomb.

### Core Features:

- Machined Gun Housing
- Wide Assortment of Electrodes
- High-Flex Air or Water-Cooled Cables
- Adjustable Pressure Trigger on Push Guns
- 36 Month Warranty
- Made in USA

### Optional Features:

- Integrated Pneumatic System
- Dual Weld Gun Connect
- Seam Welder Attachment
- Mast and Boom Station
- Certificate of Calibration
- Air over Oil Booster
- Medium and High Frequency Inverter DC
- 60-Month Extended Warranty
- Certificate of Calibration



### Full 3-Year Warranty

Company warrants equipment shall be free from defect in material and workmanship for thirty-six (36) months from date of delivery.



### Customize A Machine

Our machines can be modified to fit any custom application.

**Application**  
Foil - 2-ply  
Foil - Multi-ply  
Cross Wire  
Resistance Brazing

**Weld Material**  
Low Carbon Steel  
Nickel Alloy  
High-Temp Alloy  
Titanium  
Brass  
Copper

**Certification**  
NADCAP Compliant  
RWMA Compliant  
MIL-W- 6858 Compliant  
AWS D17.2 Compliant  
CE Certified  
CCC Certified

## Model Specifications: Handpieces

	Push Gun	Pneumatic-operated Pincer	Hydraulically-operated Pincer
<b>Available Throat Depth:</b>	N/A	2.0 (standard)	4.0 (standard)
<b>Force Range (nominal):</b>	N/A	15-100 lbs @ 80 PSI	250 lbs @ 55 PSI (Requires Hydraulic Booster)
<b>Weld Type:</b>	Spot/Seam	Spot	Spot
<b>Approx. Gun Weight:</b>	14 oz	24 oz - 4 lbs	6 lbs
<b>Cooling:</b>	Air or Water	Air or Water	Water

## Model Specifications: Power Supplies

	WD5K	WD8K	WD20K
<b>O/P Process:</b>	Single-Phase AC	Single-Phase AC	Single-Phase AC
<b>Control:</b>	EN2000	EN2000	EN1000
<b>KVA @ 50% D.C.:</b>	5	8	20
<b>Dimensions:</b>	14" x 19" x 21" (W x D x H)	14" x 19" x 21" (W x D x H)	19" x 32" x 46" (W x D x H)
<b>Weight:</b>	75 lbs	85 lbs	150 lbs
<b>Cooling:</b>	Air or Water	Water	Water

### Standard Specifications: Production Ready

<b>O/P Process</b>	Single-Phase AC / Medium Frequency Inverter DC
<b>Weld Timer:</b>	Microprocessor-driven
<b>Power Requirements</b>	230VAC / 380VAC / 480VAC / 600VAC - 50 / 60 Hz (P)

Seedorff ACME assumes no responsibility for any errors that may appear in the publication. Product, pricing and feature information contained herein is subject to change without notice.